

PRODUCT DATA SHEET

Product Code **SL-1000**

BASE CLOTH: **1000D HIGH TENACITY AIR TEXTURED
FILAMENT NYLON**

COATING TYPE: **Polyurethane**

USEABLE WIDTH: **145CM**

TEST	METHOD	REQUIREMENT	RESULT
MASS	AS 2001.2.13	360 G/M2	360 +/-10%
BREAKING FORCE	AS 2001.2.3.1	LENGTH 3000N WIDTH 2500N	4103 2714
BREAKING FORCE AFTER 672 HOURS UV EXPOSURE	AS 2001.21	LENGTH 1800N WIDTH 1500N	3369 2284
TEARING FORCE	AS 2001.2.10	LENGTH 140N WIDTH 140N	254 170
WATER RESISTANCE	AS 2001.2.17	10 KPA	10 PLUS
CONE TEST	AS 2001.2.18	NIL	ZERO LEAKAGE
WATER REPELLENCY (SPRAY RATING)	AS 2001.2.16	90	100
COLOR FASTNESS TO LIGHT	AS2001.4.21	4	4-5
COLOR FASTNESS TO RUBBING	AS2001.4.3	DRY 4 WET 4	5 5
RESISTANCE TO FLEX ABRASION	DEF (AUST) 5037	6000 CYCLES	NO ABSORPTION
RESISTANCE TO HEAT (BLOCKING)	DEF (AUST) 5037	120 GRAMS	NO DAMAGE

SPEEDLINE TEXTILES P/L
C/- Storage King Dandenong Bld
7/22 Carter Way
Dandenong South Vic 3175

Ph [03] 9702 7563
Fax [03] 9702 7564

speedlinetextiles@gmail.com
Robert Krivaci – Mobile 0417 244 004