

PRODUCT DATA SHEET

Product Code

SL-300

Product Description

300D Polyester Oxford PU Coated

TEST	SPECIFICATION	TEST METHOD
Base Fabric	100% Polyester	
Weight	190 g/m2	AS 2001.2.13
Width	153cm	
Water Resistance	150Kpa	AS 2001.2.17
Spray Rating	100	AS 2001.2.16
Breaking Force Warp N	1250	AS 2001.2.3.1
Breaking Force Weft N	1200	AS 2001.2.2.1
Tearing Force Warp N	52	AS 2001.2.10
Tearing Force Weft N	52	AS 2001.2.10
Light Fastness	6 Blue Wool Method	AS1512 Part A
Color Fastness	5 to Sea Water	AS 1512 Part B
Washing Fastness	Min 4	ISO 105 E01

DISCLAIMER

The information contained in the product Data Sheet is based on results obtained on the sample assessed at the time in accordance with the method provided. The values are a guide to purchasers of the Fabric to evaluate the Fabric and determine its suitability for their products intended end use

SPEEDLINE TEXTILES P/L
C/- Storage King Dandenong Bld
7/22 Carter Way
Dandenong South Vic 3175

Ph [03] 9702 7563
Fax [03] 9702 7564

speedlinetextiles@gmail.com
Robert Krivaci – Mobile 0417 244 004